



CE **STAFOR Ltd**
 Model: STAFOR 5-10 SI
 230 V~ 1N 5-10 kW IP44
 not to exceed 50 Hz
 liquid conductance not to exceed 230 µS at a temp. of 15°C
 worldwideregistry (patented) good
 Made in EU
 ne varata per 50 Hz
 likvidna vodljivost ne prekorači 230 µS pri temp. 15°C
 Vissesiddele potestas
 Isgatayads ES
 Spannung max. 50 Hz
 Maximale Energieaufnahme der Flüssigkeit
 230 µS bei 15°C nicht überschreiten
 Wollpatentiert
 Made in EU
 WWW.STAFOR.EU

WARNING: Before obtaining access, all supply electrical must be disconnected. Hot surface!
UZMANIBU: Prije nego što pristupite, morate odvojiti električnu opremu. Vruća površina!
WARNUNG: Vor Arbeiten Stromzufuhr unterbrechen. Verbrennungsgefahr!
 Do not use water!
 Nekištiti odens!
 Verwenden Sie kein Wasser!

Erdung obligatorij
 Završetak obligatorij
 Erdungsleitung obligatorisch
Natural circulation
 Dablogi cirkulacijat
 Naturkreislauf!

APPROVED			
CHECKED			
DRAWN			
RESP.	INITIAL	DATE	SIGN



ION HEATERS
STAFOR
 HIGH ENERGY EFFECTIVITY

Important:	FILE Ion boiler (heater) STAFOR 5-10kW SCREW IN, 1P TITLE Ion boiler (heater) STAFOR 5-10kW SCREW IN, 1P
DWG.NO. 5-10.SI.1	REVISION
SHEET 1/1	SCALE